



# HBC Meister®

The Professional's Choice

## Technical Data Sheet



1

K

P

R

I

M

E

R

S

### PRODUCT DESCRIPTION

HBC Meister Adhesion Aid (Plastic Primer) is a fast drying clear universal adhesion promoter to help bond to difficult substrates and to provide a surface suitable for the subsequent applications of any of our HBC Meister Primers, topcoats or clearcoats.

Can be used on aluminium, steel, stainless steel, galvanised steel, tinplate, PVC, melamine, laminates, glass and porcelain.

Can also be used as a plastic primer on rigid, non-porous plastics commonly used in the automotive industry.

### DIRECTIONS FOR USE

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc.

Mask off with masking paper and masking tape to prevent any overspray.

Use between 15 to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the adhesion aid is thoroughly mixed.

Repeat shaking at regular intervals during use. Spray from a distance of 20cm to 25cm.

Apply two very light coats with up to 10-15 minutes intervals between coats and leave for 20 minutes at 20°C prior to the application of our HBC Meister Primer.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time.

### PART NUMBERS

325056 Adhesion Aid Plastic Primer



This information is provided in good faith, relying on data and sources deemed reliable. The Company cannot assume responsibility for the ultimate performance of this product, as external conditions beyond our control may impact its outcome.

Cumbrian Marketing Ltd  
Townfoot Industrial Estate  
Brampton CA8 1SW  
Cumbria

Phone: (+44) 0169 7741 080  
Email: hbcmeister@cumbrian.co.uk  
www.hbcmeister.co.uk

