



HBC Meister®

The Professional's Choice

Technical Data Sheet



1
K

C
L
E
A
R

C
O
A
T
S

PRODUCT DESCRIPTION

HBC Meister Lacquer spray is a fast drying tough durable acrylic lacquer for the overcoating of base-coat paint systems.

With good protection against weathering, it is ideal for a quick repair on cars, commercial vehicles and many other industries.

DIRECTIONS FOR USE

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Allow previous applied base-coat to dry for approx 30 minutes, do not leave any longer or you will get adhesion problems.

Use between 15°C to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the lacquer is thoroughly mixed.

Repeat shaking at regular intervals during use. Spray from a distance of 20cm to 25cm.

Apply the lacquer in several light coats with up to 10 minute intervals between coats to achieve the best results.

The number of coats depends on the colour being overcoated. Leave for 24 hours at 20°C to harden.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time.

PART NUMBERS

325047 Clear Lacquer

325050 Matt Lacquer



This information is provided in good faith, relying on data and sources deemed reliable. The Company cannot assume responsibility for the ultimate performance of this product, as external conditions beyond our control may impact its outcome.

Cumbrian Marketing Ltd
Townfoot Industrial Estate
Brampton CA8 1SW
Cumbria

Phone: (+44) 0169 7741 080
Email: hbcmeister@cumbrian.co.uk
www.hbcmeister.co.uk

