

Technical Data Sheet









PRODUCT DESCRIPTION

HBC Meister High Build & Etch Primer, is a fast drying, self etching high build & etch primer with high filling power and protection against corrosion.

Adheres to Iron, Zinc, Steel, Aluminium and most recoatable plastics. Ideal for a quick repair on cars, commercial vehicles and many other industries.

Can be overcoated with 1K, 2K or waterbased paints.

DIRECTIONS FOR USE

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc.

Lightly abrade the surface, mask off with masking paper and masking tape to prevent any overspray.

Use between 15°C to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the primer is thoroughly mixed.

Repeat shaking at regular intervals during use. Spray from a distance of 20cm to 25cm.

Apply several light coats with up to 10 minutes intervals between coats to achieve the best results.

The number of coats depends on the colour that is being over painted. Sandable after approx 30 minutes at 20°C.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time.

PART NUMBERS

325052 High Build & Etch Black 325053 High Build & Etch White 325051 High Build & Etch Light Grey 325351 High Build & Etch Dark Grey

This information is provided in good faith, relying on data and sources deemed reliable.

The Company cannot assume responsibility for the ultimate performance of this product, as external conditions beyond our control may impact its outcom











Cumbria