



HBC Meister®

The Professional's Choice

Technical Data Sheet



1
K

A
C
R
Y
L
I
C

S
P
R
A
Y
S

PRODUCT DESCRIPTION

HBC Meister High Quality Wheel Silver is a fast drying tough durable acrylic spray with good protection against weathering and yellowing for wheel rims and other vehicle parts.

It is recommended to use our HBC Meister High Build & Etch Primer as an undercoat.

DIRECTIONS FOR USE

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc.

Mask off with masking paper and masking tape to prevent any overspray.

Use between 15 to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the paint is thoroughly mixed.

Repeat shaking at regular intervals during use.

Spray from a distance of 20cm to 25cm.

Apply several light coats with up to 10 minute intervals between coats to achieve the best results.

The number of coats depends on the colour of the primer being overcoated. Leave for 24 hours at 20°C to harden.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time.

PART NUMBERS

325055 High Quality Wheel Silver

This information is provided in good faith, relying on data and sources deemed reliable. The Company cannot assume responsibility for the ultimate performance of this product, as external conditions beyond our control may impact its outcome.

Cumbrian Marketing Ltd
Townfoot Industrial Estate
Brampton CA8 1SW
Cumbria

Phone: (+44) 0169 7741 080
Email: hbcmeister@cumbrian.co.uk
www.hbcmeister.co.uk

