



HBC Meister®

The Professional's Choice

Technical Data Sheet



1
K
A
C
R
Y
L
I
C
S
P
R
A
Y
S

PRODUCT DESCRIPTION

HBC Meister 1K Acrylic is a fast drying tough durable acrylic top coat with good protection against weathering, ideal for a quick repair on cars, commercial vehicles and many other industries.

It is recommended to use our HBC Meister 1K Acrylic as an undercoat or our HBC Meister High Build & Etch Primer if painting over bare metal or a recoatable plastic.

DIRECTIONS FOR USE

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc.

Mask off with masking paper and masking tape to prevent any overspray.

Use between 15 to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the paint is thoroughly mixed.

Repeat shaking at regular intervals during use. Spray from a distance of 20cm to 25cm.

Apply several light coats with up to 10 minute intervals between coats to achieve the best result.

The number of coats required depends on the colour being painted.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time. If sprayhead should clog, remove and clean with solvent.

PART NUMBERS

325042 Satin Black

325043 Matt Black

325048 Gloss White

325044 Gloss Black

This information is provided in good faith, relying on data and sources deemed reliable. The Company cannot assume responsibility for the ultimate performance of this product, as external conditions beyond our control may impact its outcome.

Cumbrian Marketing Ltd
Townfoot Industrial Estate
Brampton CA8 1SW
Cumbria

Phone: (+44) 0169 7741 080
Email: hbcmeister@cumbrian.co.uk
www.hbcmeister.co.uk

