



HBC Meister®

The Professional's Choice

Technical Data Sheet



1

K

A

C

R

Y

L

I

C

S

P

R

A

Y

S



PRODUCT DESCRIPTION

HBC Meister Texture Black gives a structured coating directly onto rigid plastics, such as bumpers, spoilers and exterior mirrors.

Ideal for a quick repair on cars, smart repair, commercial vehicles and many other industries.

For best results an application of our HBC Meister Adhesion Aid (Plastic Primer) is recommended prior to applying the texture black.

DIRECTIONS FOR USE

SHAKE CAN FOR AT LEAST TWO MINUTES BEFORE USE

Prepare the area to be painted, ensuring it to be free from dirt, wax, oil, etc., using a quality degreaser.

Mask off with masking paper and masking tape to prevent any overspray.

Use between 15°C to 25°C in a well ventilated area.

Shake can vigorously for at least two minutes to ensure the product is thoroughly mixed.

Repeat shaking at regular intervals during use.

Spray from a distance of 20cm to 25cm. For best results on plastics, an application of our HBC Meister Adhesion Aid (Plastic Primer) is recommended prior to spraying the texture black.

Apply several light coats with up to 10 minute intervals between coats to achieve the best result.

Allow to dry for 24 hours at 20°C to fully harden.

If over-coating with another 1K colour, allow to dry for 4 hours prior to re-coating, then allow to dry for the stated 24 hours.

After use invert can and spray to clear the valve and sprayhead, this prevents the aerosol from clogging up prior to using next time.

PART NUMBERS

325058 Texture Black

This information is provided in good faith, relying on data and sources deemed reliable. The Company cannot assume responsibility for the ultimate performance of this product, as external conditions beyond our control may impact its outcome.

Cumbrian Marketing Ltd
Townfoot Industrial Estate
Brampton CA8 1SW
Cumbria

Phone: (+44) 0169 7741 080
Email: hbcmeister@cumbrian.co.uk
www.hbcmeister.co.uk

